- (e) Method 3 is used for gas analysis;
- (f) Method 4 is used for stack gas moisture;
- (g) Methods 2, 2A, 2C, or 2D; 3; and 4 shall be performed, as applicable, at least twice during each test run.

§ 60.746 Permission to use alternative means of emission limitation.

- (a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions of VOC from any emission point subject to §60.742(c) at least equivalent to that required 60.742(b)(2) or 60.742(c), respectively, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means. The Administrator may condition permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emission reduction as specified in §60.742(b)(2) or $\S60.742(c)$, respectively.
- (b) Any notice under paragraph (a) of this section shall be published only after public notice and an opportunity for a public hearing.
- (c) Any person seeking permission under this section shall submit to the Administrator either results from an emission test that accurately collects and measures all VOC emissions from a given control device or an engineering evaluation that accurately determines such emissions.

§ 60.747 Reporting and recordkeeping requirements.

- (a) For each affected facility subject to the requirements of §60.742(b) and (c), the owner or operator shall submit the performance test data and results to the Administrator as specified in §60.8(a) of this part. In addition, the average values of the monitored parameters measured at least every 15 minutes and averaged over the period of the performance test shall be submitted with the results of all performance tests.
- (b) Each owner or operator of an affected facility subject to the provisions specified in §60.742(c)(3) and claiming to use less than 130 Mg of VOC in the first year of operation and each owner or operator of an affected facility claiming to use less than 95 Mg of VOC

- in the first year of operation shall submit to the Administrator, with the notification of anticipated startup required under §60.7(a)(2) of the General Provisions, a material flow chart indicating projected VOC use. The owner or operator shall also submit actual VOC use records at the end of the initial year.
- (c) Each owner or operator of an affected facility subject to the provisions of \$60.742(c)(3) and initially using less than 130 Mg of VOC per year and each owner or operator of an affected facility initially using less than 95 Mg of VOC per year shall:
- (1) Record semiannual estimates of projected VOC use and actual 12-month VOC use:
- (2) Report the first semiannual estimate in which projected annual VOC use exceeds the applicable cutoff; and
- (3) Report the first 12-month period in which the actual VOC use exceeds the applicable cutoff.
- (d) Each owner or operator of an affected facility demonstrating compliance by the methods described in §60.743(a)(1), (2), (4), (b), or (c) shall maintain records and submit quarterly reports to the Administrator documenting the following:
- (1) For those affected facilities monitoring only the carbon adsorption system outlet concentration levels of organic compounds, the periods (during actual coating operations) specified in paragraph (d)(1)(i) or (ii) of this section, as applicable.
- (i) For carbon adsorption systems with a common exhaust stack for all the individual adsorber vessels, all periods of three consecutive system rotations through the adsorption cycles of all the individual adsorber vessels during which the average value of the concentration level of organic compounds in the common outlet gas stream is more than 20 percent greater than the average value measured during the most recent performance test that demonstrated compliance.
- (ii) For carbon adsorption systems with individual exhaust stacks for each adsorber vessel, all 3-day rolling averages for each adsorber vessel when the concentration level of organic compounds in the individual outlet gas stream is more than 20 percent greater